



## Dane techniczne:

Technical data:

Typ Type	Przekrój Profile	h [m]	b [mm]	a [mm]	a/b [mm]	a/b [mm]	h [mm]	B [mm]	[kg]
SO 3/3	○	3	3	60/156	100/400	310	B-80	28	
SR 3	○	3	4	60/133	100/400	400	-	40	
SR 3-F	○	3	4	60/133	100/400	400	B-80	31	
C 3/3	◎	3	3	60/100	70/400	500	B-80	22	
SO 3,5/3	○	3,5	3	60/156	100/400	310	B-80	31	
SR 3,5	○	3,5	4	60/133	100/400	400	-	44	
SR 3,5-F	○	3,5	4	60/133	100/400	400	B-80	33	
C 3,5/3	◎	3,5	3	60/106	70/400	500	B-80	26	
SO 4/3	○	4	3	60/156	100/400	500	B-80	38	
SR 4	○	4	4	60/133	100/400	400	-	48	
SR 4-F	○	4	4	60/133	100/400	400	B-80	36	
C 4/3	◎	4	3	60/111	70/400	500	B-80	31	
SO 4,5/3	○	4,5	3	60/156	100/400	500	B-80	44	
SR 4,5	○	4,5	4	60/133	100/400	400	-	53	
SR 4,5-F	○	4,5	4	60/133	100/400	400	B-80	41	
C 4,5/3	◎	4,5	3	60/119	70/400	500	B-80	36	
SO 5/3	○	5	3	60/156	100/400	500	B-80	48	
SX 5/3	○	5	3	60/191	100/400	500	B-120	59	
SX 5/4	○	5	4	60/191	100/400	500	B-120	74	
SR 5	○	5	4	60/133	100/400	400	-	59	
SR 5-F	○	5	4	60/133	100/400	400	B-80	47	
C 5/3	◎	5	3	60/124	70/400	500	B-80	39	
C 5/4	◎	5	4	60/124	70/400	500	B-120	71	

- - ośmiokąt / octagonal-conical
- - rura / tubular
- ◎ - stożek / round-conical

