

9000 PTZ Internal & External IP Dome Cameras

An integration of excellent sensors and world class H.264 compression delivers a milestone in the evolution of IP video

IndigoVision's range of 9000 PTZ IP dome cameras are designed to be used with the company's complete end-to-end IP Video solution and have class-leading H.264 compression technology built-in. The 9000 PTZ cameras are fully compatible with IndigoVision's Control Center Video and Alarm Management software and its range of Network Video Recorders (NVRs).

- ☐ Internal or external, day/night
- ☐ Class-leading H.264 compression delivering high quality video at exceptionally low bit rates
- ☐ Progressive or Interlace scan options 18x, 35x and 36x optical zoom
- ☐ Wide dynamic range
- ☐ Outstanding low light performance
- ☐ Image Stabilization



Pendant Camera with optional wall mount



In-Ceiling Mount

Specification

General Specifications



Zoom order options	36x optical + 12x digital	35x optical + 12x digital	18x optical + 12x digital
Lens	3.4mm to 122.4mm, F1.6 to F4.5	3.4mm to 119mm, F1.4 to F4.2	4.1mm to 73.8mm, F1.4 to F3.0
Scan Mode	Interlaced	Progressive or Interlaced	Interlaced
Horizontal View Angle	1.7° to 57.8°	1.7° to 55.8°	2.8° to 48°
Day/Night	Yes	Yes	Yes
Wide dynamic range	Yes	Yes	Yes
Image Stabilizer	No	Yes	No
Min Sensitivity	NTSC, F1.6, 50 IRE 0.1 lx at 1/4 sec (color) 0.01 lx at 1/4 sec (mono) PAL, F1.6, 50 IRE 0.1 lx at 1/3 sec (color) 0.01 lx at 1/3 sec (mono)	NTSC, Interlace, F1.4, 35 IRE 0.05 lx at 1/4s (color) 0.01 lx at 1/4s (mono) PAL, Interlace, F1.4, 35 IRE 0.05 lx at 1/3s (color) 0.01 lx at 1/3s (mono)	NTSC, F1.4, 50 IRE 0.07 lx at 1/4 sec (color) 0.01 lx at 1/4 sec (mono) PAL, F1.4, 50 IRE 0.07 lx at 1/3 sec (color) 0.01 lx at 1/3 sec (mono)
Resolution	>540 TVL	>540 TVL	>540 TVL

Sensor	1/4" Sony ExView HAD	Video Compression	Full frame rate H.264 (ISO 14496-10): 25/30fps guaranteed												
Active Pixels	752(H) x 582(V)	Dual Encoding	<table><tr><td></td><td>A</td><td>B</td></tr><tr><td>4SIF</td><td>1 stream</td><td>1 stream</td></tr><tr><td>2SIF</td><td>2 streams</td><td>2 streams</td></tr><tr><td>SIF</td><td>3 streams</td><td>3 streams</td></tr></table>		A	B	4SIF	1 stream	1 stream	2SIF	2 streams	2 streams	SIF	3 streams	3 streams
	A		B												
4SIF	1 stream		1 stream												
2SIF	2 streams		2 streams												
SIF	3 streams		3 streams												
Signal/noise ratio	>50 dB	Combine one selection from column A plus one selection from column B: e.g. 1x4SIF stream plus 2x2SIF streams													
Shutter/Iris/Focus	Automatic with manual override														
Manual Shutter Speeds	1 to 1/10000 sec.	Video Bitrate	User configurable from 32Kbps to 8Mbps												
White Balance/Gain/IR Filter	Automatic	Multi-Streaming	Up to 16 simultaneous unicast video users plus unlimited multicast users												
Standard Pendant and In-Ceiling Electrical	Operating voltage: 24V AC/DC @ 1A Power consumption: 24W; Surge protection 24V DC power supply included	Resolution	SIF: 352x288 pixels (PAL); 352x240 pixels (NTSC) 2SIF: 704x288 pixels (PAL); 704x240 pixels (NTSC) 4SIF: 704x576 pixels (PAL); 704x480 pixels (NTSC)												
Environmental Pendant Electrical	Operating Voltage: 24V AC/DC @ 2.3 A Power Consumption: 55W; Surge protection 24V DC power supply included	Network Protocols	TCP, UDP, IGMP, SNMP, HTTP, FTP, NTP												
Console Input/Output	RS232	Network Interface	This camera complies with IEEE 802.3u 100BASE-TX Fast Ethernet, with the exception that cable length is limited to 70m. The camera must be installed such that the length of the cable run between the Ethernet switch and the camera is 70m or less.												
Weight	In-Ceiling: 2.7 Kg Standard Pendant: 5.5 Kg Environment Pendant: 5.7 Kg	Network Security	Embedded Linux firewall												
Pendant Construction	Vandal resistant die-cast aluminium	Time	Embedded real-time clock, NTP client												
Bubble Construction	Optical grade polycarbonate	Features													
Storage Temp (All Models)	-20°C (-4°F) to +70°C (158°F)	Presets	250												
In-Ceiling Operating Temperature	0°C (32°F) sustained minimum +40°C (104°F) sustained maximum	Preset Accuracy	0.05°												
Standard Pendant Operating Temperature	-5°C (23°F) sustained minimum +60°C (140°F) absolute maximum for periods of 1 hour +50°C (122°F) sustained maximum	Preset Tours	100 each with 20 presets												
Environmental Pendant Operating Temperature	-20°C (-4°F) sustained minimum +60°C (140°F) absolute maximum for periods of 1 hour +50°C (122°F) sustained maximum	Pattern/Mimic Tours	4 each with up to 1 minute												
Ingress Protection	IP67	Pan Range	360° continuous rotation												
Regulatory	EN 55022(1994) ITE emission standard Class A EN 55024(1998) ITE immunity standard Class A (US federal code of regs) EN 61000-3-2(1995) mains harmonics Class A EN 61000-3-3(1995) voltage fluctuation CFR47(1995) Part 15 subpart B UL2044 (In-Ceiling with Plenum Rated Back Box)	Tilt Range	-5° (above horizontal) to +90° (vertically down)												
Binary Input/Output	2 opto-isolated inputs; 1 solid state opto-isolated relay output	Pan/Tilt Speed	0.001°/s to 360°/s												
		Preset Move Speeds	200°/s												
		Privacy Zones	24 User Defined												
		Picture Freeze option	Yes												
		Image Flip	Yes												


FCCE




9000 PTZ Pendant IP Domes




Swan Neck Mount




Wall Mount




0.5m Vertical Pipe




Pole Mount Adaptor




Sun Shroud



1.5" NPT Male Adapter




1.5" NPT Female Adapter




Corner Mount Bracket

Pendant cameras ship with no mounts.
Mounts and accessories are separately orderable.


9000 PTZ In-Ceiling IP Domes




In-Ceiling Dome



Hole Cutting Dimensions



Surface Mount for In-Ceiling Dome



Plenum Rated Back Box for In-Ceiling Dome

Easy Installation

